
Blaze Square Light Box 1002 - Hanging

The Blaze™ Hanging Square 1002 is an eye-catching and commanding hanging structure that transforms interior environments such as retail stores, restaurants, workplace offices, tradeshows, and more. This display is suspended from the ceiling and beams from above. The size of this structure is 10' wide by 10' long and 2' tall; each side has full-perimeter light bars. Easily push-fit the double-sided SEG fabric graphic into each side of the frame for a seamless look.

Two backlit graphic material options are available to choose from,



features and benefits:

- 6'' aluminum silver frame
- Perimeter LED light bars attached to the frame feature an internal power supply
- Easy-to-change double-sided SEG push-fit graphics
- Hanging cables included
- UL Certified & ADA compliant sizing; approved for public spaces
- 5 year LED warranty on lights; long life span
- 43,800 hours for 5 years if powered 24/7
- Comes in a box or case

dimensions:

Hardware

Assembled unit:

120”w x 24”h x 120”d
3048mm(w) x 610mm(h) x 3048mm(d)

Approximate Weight:
190 lbs / 86 kg

Graphics

Graphic material: Backlit Textile (dye-sublimated fabric)

See graphic templates for graphic sizes.

Refer to related graphic templates for more information Visit:

https://www.theexhibitorshandbook.com/downloads/download-graphic-templates
or click here

Shipping

Packing - 5 Boxes:
Shipping dimensions:
4 x BOX: 78"L x 9"H x 8"D
(1981mm x 229mm x 203mm)
1 x BOX: 24"L x 10"H x 12"D
(610mm x 254mm x 305mm)

Approximate shipping weight: 210lbs / 95kg

Packed in optional OCE2 Case:
Shipping dimensions:
3 x BOX - 17"L x 63"H x 17"D
431.8mm(l) x 1600mm(h) x 431.8mm(d)

Approximate shipping weight:
295 lbs / 133.8 kg

additional information:

Silver finish only



We are continually improving and modifying our product range and reserve the right to vary the specifi cations without prior notice. All dimensions and weights quoted are approximate and we accept no responsibility for variance. E&OE. See Graphic Templates for graphic bleed specifications

Tools Required



MULTI HEX KEY
(INCLUDED)





PHILLIPS SCREW DRIVER
(NOT INCLUDED)





1/2" WRENCH
(NOT INCLUDED)

PART NUMBER	DESCRIPTION	QTY.
343-578-76-76	343 CORNER EXTRUSION 587mm	4
360-1524-02-74	1524mm LENGTH OF 360 EXTRUSION WITH (2) IB2 HOLE ONE END AND MITER CUT (2) CB9 HOLE ONE END	4
360-1524-02-75	1524mm LENGTH OF 360 EXTRUSION WITH (2) IB2 HOLE ONE END AND REVERSE MITER CUT (2) CB9 HOLE ONE END	4
360-1524-02-46-75	1524mm LENGTH OF 360 EXTRUSION WITH (2) IB2 HOLES ONE END AND REVERSE MITER CUT WITH (2) CB9 HOLES ONE END, (2) UBOLT HOLES	4
360-1524-02-58-74	1524mm LENGTH OF 360 EXTRUSION WITH (2) IB2 HOLES ONE END AND MITER CUT WITH (2) CB9 HOLES ONE END, (2) UBOLT HOLES, GROMMET HOLE	4
101-578-01-01-60-PW	578MM OF PH1 POWDER COAT EXTRUSION WITH CAMLOCKS HOLE AND BLZ BRKT BOTH ENDS	4
343-EC-INNER	ENDCAP 343-INNER	8
343-EC-OUTER	ENDCAP 343 OUTER	8
IB2-0	IB2-0 INLINE CONNECTOR	16
CB9	CB9 CORNER BRACKET	16
LED-EV-WHT-6000-10	10" LED LIGHT FIXTURE	48
LED-EV-THUMB-ORB	THUMB KNOB, ORBUS VERSION, FOR LED LIGHT BAR	96
BLZ-U-BOLT	5/16-18 GRADE 2 min. HARDENED STEEL U-BOLT WITH (4) WASHERS, (2) Medium-Strength Steel Hex Nut, (2) Medium-Strength Steel Nylon-Insert Lock-nut	8
CH-ID-HD-08	INDIVIDUAL CABLE HEAVY DUTY HARNESS WITH 96" LENGTHS 1/8" CABLE	8
1/4-20-8H-SCW-1	1/4-20-SHCS-SCW-1, 18-8 Stainless Steel Button Head Hex Drive Screw	8
1/4-20-WING-NUT	1/4-20-WING-NUT, Zinc-Plated Steel	8
1/4-FENDER-WASHER	92141A030	8
BLZ-BRKT	BLAZE SPREADER BRACKET- Aluminum,white RAL#9003	16
SLIM STL SAFE LOCK	SLIM STEEL, SAFETY CHANNEL LOCK	16
1/4-20-8H-SCW-1/2	1/4-20-SHCS-SCW-.5, 18-8 Stainless Steel Button Head Hex Drive Screw	16










How to Apply & Remove Graphics


Installation and removal of SEG graphics is easy!

Installation: Push the SEG bead into each corner of the frame (1-4) with your thumb, then push the SEG bead into the middle of the run (5-8) and work your way around the perimeter of the frame until all beading is pushed in properly; if necessary, go around the perimeter again to ensure beading is secure in the extrusion profile.



Note: Keep the set up area clean by using a drop cloth, washing hands before set-up or by wearing gloves.

Removal: Use the pull tab located on the graphic and gently pull the graphic from the frame, going around the perimeter.



Graphics Storage & Care

Graphics should be folded with the graphic facing inward and stored in a zip lock /sealable plastic bag. Spot clean by wiping with a damp white cloth. If washing is necessary, use a commercial size front-loading washing machine, gentle cycle with cool water. Line dry flat. Dry cleaning is NOT recommended to prevent shrinkage.